



# AXIS AXTX3-60

Integrated RF Camera Transmitter System with Camera "Paint" Control

RF Frequency Bands	2GHz to 7.1GHz
Camera RF Output	Selectable to 10, 50, 100mW
DVB-T Bandwidth	6,7,8MHz
DVB-T Guard	1/32, 1/16, 1/8, 1/4
DVB-T FEC	1/2, 2/3, 3/4, 5/6, 7/8
DVB-T Constellations	QPSK, 16QAM, 64QAM
Video Input	SD/HD-SDI/3G-SDI/1080p
Compression Type	AVC/H.264/MEPG-4 Part 10
Encoder Latency	20mS In Ultra Low Delay
Encoder Bitrates	0.25 to 31Mb/s COFDM
Audio Inputs	SD/HD-SDI Embedded
Power – DC Input	6 to 17VDC
Power Consumption	10W
Available Battery Plates	Anton Bauer
Camera "Paint" Receiver	Mounted inside the AXIS AXTX3-60
Frequency	403-474 MHz



### 3G Resolutions

1920x1080p 60/59.94/50Hz  
(via Level A or Level B Dual Link)

### HD Resolutions

1920x1080i 60/59.94/50Hz  
1920x1080p 30/29.97/25/24/23.97Hz  
1920x1080psf 30/29.97/25/24/23.97Hz  
1280x720p 60/59.94/50Hz

### SD Resolutions

720x480i 59.94Hz, 720x576i 50Hz

99 Garden Parkway Suite C, Carlisle, PA 17013  
PH: 1.888.736.9283

www.wavecentralrf.com

Specifications subject to  
Change without prior notice.

112117-A