



AXRX-QDM

Portable 2way Diversity COFDM H.264 Receiver

RF Inputs (2)	2GHz to 6GHz
RF Input Connectors (2)	N-Female
DVB-T Bandwidth	6,7,8MHz
DVB-T Guard	1/32, 1/16, 1/8, 1/4
DVB-T FEC	1/2, 2/3, 3/4, 5/6, 7/8
DVB-T Constellations	QPSK, 16QAM, 64QAM
Sensitivity	-95dB plus
RS232 GUI Control	9-pin D-type
Video Output	(2) SDI/HD-SDI Video, (1) Composite – BNC (f) IP Streaming/Control RJ45
Audio Output	Analog (2) Stereo Line Level via 5pin 0B Lemo Embedded
Video Line Standard	PAL/NTSC
Resolution (HD)	HD Resolutions 1920x1080i 60/59.94/50Hz 1920x1080p 30/29.97/25/24/23.97Hz 1920x1080psf 30/29.97/25/24/23.97Hz 1280x720p 60/59.94/50Hz SD Resolutions 720x480i 59.94Hz, 720x576i 50Hz
Power Consumption	20 Watts
Power – DC Input	9 to 16VDC
Available Battery Plates	IDX or Anton Bauer



99 Garden Parkway Suite C, Carlisle, PA 17013
PH: 1.888.736.9283

www.wavecentralrf.com

22017-A

Specifications subject to
Change without prior notice.