



AXIS 4K - TRANSPORT

Portable HEVC H.265 Encoder / Decoder



Remote	IP Web GUI
Video Output	(1) SDI/HD-SDI Video - BNC (f) IP Streaming/Control RJ45
Audio	Embedded, MPEG-1 Layer2, AAC-LC, HE-AAC 8 Pairs, Analog Audio 2 pairs line/mic level
Legacy Encoding	H.264 & MPEG2
Resolution Profiles	4K UHD. 4:2:2/4:2:0, 8/10-bit 2160p: 23.98, 24, 25, 29.97, 30, 50, 59.94, 60 HD. 4:2:2/4:2:0, 8/10-bit 720p: 50, 59.94, 60 1080i: 50, 59.94, 60 1080p: 23.98, 24, 25, 29.97, 30, 50, 59.94, 60 SD 4.2.2/4.2.0 480i: 29.97 576i: 25
Latency Encoder to Decoder	60ms (90ms in 4K mode)
Power – DC Input	9 to 18VDC
Size	W: 5 in / L: 7.125 in / H: 1.5 in



HEVC Encoder Rear Panel



HEVC Decoder Rear Panel

99 Garden Parkway Suite C, Carlisle, PA 17013
PH: 1.888.736.9283

www.wavecentralrf.com

Specifications subject to
Change without prior notice.

2618-A